



InfraStruXure® PDU 80kW 480V/208V W/ MBP

Part Number: PD80G6FK1-M



Output

Nominal Output Voltage	120V,208V 3PH
Maximum Total Current Draw per Phase	277.5A

Input

Nominal Input Voltage	480V 3PH
Input Frequency	60 Hz +/- 3 Hz
Number of Power Cords	1
Maximum Input Current per phase	135A
Load Capacity	80 kVA
Maximum Crest Factor	3

Physical

Net Weight	1628.00 lbs. (740.00 kg)
Maximum Height	81.00 inches (2057 mm)

Maximum Width	29.00 inches (737 mm)
Maximum depth	36.00 inches (914 mm)
Shipping Weight	1650.00 lbs. (750.00 kg)
Shipping Height	86.00 inches (2184 mm)
Shipping Width	36.00 inches (914 mm)
Shipping Depth	48.00 inches (1219 mm)
Color	Black

Environmental

Operating Environment	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3333 feet (0-999.9 meters)
Storage Temperature	5 - 113 °F (-15 - 45 °C)
Storage Relative Humidity	0 - 95%
Storage Elevation	0-30000 feet (0-9000 meters)

Conformance

Regulatory Approvals	cUL Listed,UL Listed
Standard Warranty	1 year repair or replace

Copyright © American Power Conversion Corp., all rights reserved
[About APC](#)[Investors](#)[Job Seekers](#)[Press](#)[Feedback](#)[Contact](#)[Privacy Policy](#) [RSS](#)